

## Heavy Duty Large Frame Reels Nordic Series 3700 & 5900

2", 3" or 4" fluid path for 1 1/2" through 4" I.D. hose

**Rewind:** Gear-drive crank rewind or chain and sprocket drive powered by A.C. or D.C. electric motor, compressed air motor or hydraulic motor.


**Inlet:** 2" (Series 3700) / 3" (Series 5900) straight grooved fitting is standard. 4" (Series 5900) 90° grooved fitting and 24" diameter drum is standard. 90° grooved fitting swivel joint available at extra cost.

**Gooseneck:** 2" (Series 3700) / 3" (Series 5900) / 4" (Series 5900) female NPT. Other sizes and/or threads can be furnished and must be specified.

Series 5900 product temperatures from -50 °F to +400 °F and standard pressures to 300 psi. Series 3700 standard seals maximum temperature 174 °F (79 °C) and minimum temperature -20 °F (-29 °C). Extreme temperature seals maximum temperature 400 °F (204 °C) and minimum temperature -50 °F (-45 °C).



1/2" pitch chain  
now standard



Nordic Series 3700  
Shown with optional  
bevel crank.

Nordic Series 5900  
Shown with optional  
bevel crank.



Standard pressures to 300 psi. Other temperatures or pressures can be furnished at extra cost, consult manufacturer. The standard color for this series is red or gray. Add 12" to B dimension when crank is in rewind position.

**Built to order, not returnable.**

Hose I.D.		1 1/2	2	2 1/2	3	4	Specification - Hose Capacity and Reel Dimensions													
Hose O.D.		2.063	2.563	3.188	3.75	4.75	KEY: CRK = hand crank; ELC = electric motor; HYD = hydraulic motor; AIR = air motor													
Model	Hose Length					Est. Weight	A	B CRK	B ELC	B AIR	B HYD	C	D	E CRK	E ELC	E AIR	E HYD	F	G	H
3700-23-20	ft	70	25			114 LB	in	24.5	23	23	23	21	26	30	33	32	32	20	15	13
	m	21	8			52 KG	mm	622	584	584	584	533	660	762	838	813	813	508	381	330
3700-25-20	ft	70	55			124 LB	in	26.5	25	25	25	25	26	30	33	32	32	20	15	14
	m	21	17			56 KG	mm	673	635	635	635	635	660	762	838	813	813	508	381	356
3700-25-24	ft	85	75			128 LB	in	26.5	25	25	25	25	30	34	37	36	36	24	15	14
	m	26	23			58 KG	mm	673	635	635	635	635	762	864	940	914	914	610	381	356
3700-25-32	ft	115	100			136 LB	in	26.5	25	25	25	25	38	42	45	44	44	32	15	14
	m	35	30			62 KG	mm	673	635	635	635	635	965	1067	1143	1118	1118	813	381	356
3700-31-12	ft	95	55			134 LB	in	32.5	31	31	31	31	24	18	22	25	24	12	15	17
	m	29	17			61 KG	mm	826	787	787	787	787	610	457	559	635	610	610	305	381
3700-31-20	ft	170	95			142 LB	in	32.5	31	31	31	31	24	26	30	33	32	20	15	17
	m	52	29			64 KG	mm	826	787	787	787	787	610	660	762	838	813	813	508	381
3700-31-26	ft	225	135			148 LB	in	32.5	31	31	31	31	24	32	36	39	38	26	15	17
	m	69	41			67 KG	mm	826	787	787	787	787	610	813	914	991	965	965	660	381
3700-39-16	ft	230	165			182 LB	in	40.5	39	39	39	39	24	22	26	29	28	16	15	21
	m	70	50			83 KG	mm	1029	991	991	991	991	610	559	660	737	711	711	406	381
3700-39-24	ft	360	250			190 LB	in	40.5	39	39	39	39	24	30	34	37	36	24	15	21
	m	110	76			86 KG	mm	1029	991	991	991	991	610	762	864	940	914	914	610	381
5900-31-16	ft		60	25	20	140 LB	in	32.5	31	31	31	31	24	22	26	29	28	16	20	17
	m		18	8	6	64 KG	mm	826	787	787	787	787	610	559	660	737	711	711	406	508
5900-31-24	ft		90	35	30	150 LB	in	32.5	31	31	31	31	24	30	34	37	36	24	20	17
	m		27	11	9	68 KG	mm	826	787	787	787	787	610	762	864	940	914	914	610	508
5900-31-32	ft		125	50	40	160 LB	in	32.5	31	31	31	31	24	38	42	45	44	32	20	17
	m		38	15	12	73 KG	mm	826	787	787	787	787	610	965	1067	1143	1118	1118	813	508
5900-36-12	ft		65	30	35	146 LB	in	37.5	36	36	36	36	24	18	22	25	24	12	20	21
	m		20	9	11	66 KG	mm	953	914	914	914	914	610	457	559	635	610	610	305	508
5900-36-16	ft		100	55	45	150 LB	in	37.5	36	36	36	36	24	22	26	29	28	16	20	21
	m		30	17	14	68 KG	mm	953	914	914	914	914	610	559	660	737	711	711	406	508
5900-39-12	ft		95	55	35	180 LB	in	40.5	39	39	39	39	24	18	22	25	24	12	20	21
	m		29	17	11	82 KG	mm	1029	991	991	991	991	610	457	559	635	610	610	305	508
5900-39-16	ft		145	90	45	200 LB	in	40.5	39	39	39	39	24	22	26	29	28	16	20	21
	m		44	27	14	91 KG	mm	1029	991	991	991	991	610	559	660	737	711	711	406	508
5900-39-24	ft		220	125	65	210 LB	in	40.5	39	39	39	39	24	30	34	37	36	24	20	21
	m		67	38	20	95 KG	mm	1029	991	991	991	991	610	762	864	940	914	914	610	508

Reelcraft's reel configurator can quickly and accurately quote standard large frame reels. Refer to page 27 for more information. Refer to page 28 to build a representative model number. Final part number assigned upon quote. Refer to chart on page 31 for weight adders and dimensions.

**Prop 65:** ⚠️ **WARNING:**  
Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).