

## Better by Design

- All models supplied with cord are complete with a 5 foot pigtail and three-prong plug (flying lead reels supplied with conduit box)
- Adjustable cord stop supplied on models with cord

### Adjustable Bumper Stop

Allows any desired length of cord to be maintained outside the reel.

### Corrosion-Resistant

Steel components are individually powder coated to virtually eliminate corrosion.


### Reelcraft offers many styles of outlets and lamps

- Single receptacle
- Duplex outlet box
- Triple tap
- R.V. plug
- Fluorescent
- Incandescent
- LED
- Flying lead

### Easy to Mount

Attaches to most structurally sound surfaces. Edges are curved for safety.

**Note:** Swing brackets should be used if cords are pulled at more than 45°, see page 47.



### Adjustable Guide Arm

Multiple guide arm positions for versatile uses and easier field adjustment.

### Enclosed Drive Spring

Drive mechanism is enclosed for protection against the environment.

### Long Life Drive Spring

Declutching arbor virtually eliminates possibility of spring damage due to reverse winding of reel spool.



### Structural Strength

Robotically welded heavy gauge steel frame.



## L 40501633

### REEL SERIES

40 = 4000 SERIES  
45 = 4500 SERIES  
55 = 5500 SERIES  
57 = 5700 SERIES  
70 = 7000 SERIES  
or 70000 SERIES

FOR REFERENCE ONLY

### WIRE SIZE

10 = 10 GAUGE  
12 = 12 GAUGE  
16 = 16 GAUGE

### LENGTH OF CORD

00 = W/O CORD  
35 = 35 FEET  
45 = 45 FEET  
50 = 50 FEET  
75 = 75 FEET  
100 = 100 FEET

### NO. OF CONDUCTORS

2 = TWO CONDUCTOR  
3 = THREE CONDUCTOR  
4 = FOUR CONDUCTOR

### STYLE NUMBERS

NONE = OPEN END  
1 = INCANDESCENT LAMP  
2 = FLUORESCENT LAMP  
3 = SINGLE RECEPTACLE  
4 = R.V. PLUG (M)  
5 = INCANDESCENT NON-SPARKING  
6x = FLUORESCENT EXPLOSION PROOF  
7 = DUPLEX OUTLET BOX (F)  
8 = FLUORESCENT WITH OUTLET  
9 = TRI TAP  
10 = LED LAMP  
X = FLYING LEAD

### Model Number Significance

This chart is for reference purposes only. Reels cannot be ordered by selecting from this chart. Please refer to selection charts on pages 38-39 or consult manufacturer for any questions about option combinations.

Model	Outside Diameter of Cord	Cord Specifications		
		AWG	mm <sup>2</sup>	# Cond. Type
600193	.320" - .530"	16	1.33	3 SJO
1-HR1004-A	.438" - .624"	12	3.32	3 SJO
600267	.645"	10	5.37	3 SO
1-HR1004	.625" - .749"	12	3.32	3 SO
3-HR1004-3	1.06" - 1.30"	6	8.00	3 SO