

# Power and Light Cord Reels | Series L 4000 / L 5000 / L 7000 / L 70000



**NEW!**  
L 70100 123 3A

Made in USA



L 4545 123 9G

## Cord Options

	<b>#3 - Single Receptacle</b> Single 15 AMP with clamp type strain relief for both 16 AWG and 12 AWG cord. NEMA 5-15R
	<b>#3A - Single Receptacle</b> Single 20 AMP. NEMA 5-20R
	<b>#3B - Twist Lock Connector</b> Single 20 AMP with twist lock connector. NEMA L5-20R
	<b>#4 - R.V. Plug</b> Male rubber plug used with recreational vehicles (RV's).
#7/7A/7B Duplex Outlet Box	<b>#7/7A/7B - Duplex Outlet Box</b> Duplex outlet box with flip-top lid. GFCI protection on #7 and 7A.
#9/9G Triple Tap	<b>#9/9G - Triple Tap</b> Molded triple tap. GFCI protection on #9G only.
X Flying Lead"/>	<b>X - Flying Lead</b> Bare cord or cable endings and conduit box.

	Model with Cord	Cord Ending	Cord Specifications				Volts	Amps	Shipping Weight		Size Index #
			AWG	mm <sup>2</sup>	# Cond.	ft m			Type	lbs	
	L 4035 163 3	Single Receptacle	16	1.33	3	35 11	SJTOW	125	13	25 11	1
	L 4050 163 3	Single Receptacle	16	1.33	3	50 15	SJTOW	125	13	26 12	1
	L 4545 123 3	Single Receptacle	12	3.32	3	45 14	SJEOOW	125	15	27 12	1
	L 5550 123 3	Single Receptacle	12	3.32	3	50 15	SJEOOW	125	15	44 20	3
	L 70075 123 3	Single Receptacle	12	3.32	3	75 23	SEOOOW	125	15	70 32	5
	L 70100 123 3	Single Receptacle	12	3.32	3	100 30	SEOOOW	125	15	74 34	5
	L 4545 123 3A	Single Receptacle	12	3.32	3	45 14	SJEOOW	125	20	28 13	1
	L 5550 123 3A	Single Receptacle	12	3.32	3	50 15	SJEOOW	125	20	44 20	3
	L 70075 123 3A	Single Receptacle	12	3.32	3	75 23	SEOOOW	125	20	70 32	5
	L 70100 123 3A	Single Receptacle	12	3.32	3	100 30	SEOOOW	125	20	74 34	5
	L 4545 123 3B	Twist Lock Connector	12	3.32	3	45 14	SJEOOW	125	20	28 13	1
	L 5550 123 3B	Twist Lock Connector	12	3.32	3	50 15	SJEOOW	125	20	44 20	3
	L 70075 123 3B	Twist Lock Connector	12	3.32	3	75 23	SEOOOW	125	20	70 32	5
	L 70100 123 3B	Twist Lock Connector	12	3.32	3	100 30	SEOOOW	125	20	74 34	5
	L 5750 103 4	R.V. Plug	10	5.37	3	50 15	SOOW	125	30	50 23	4
	L 4545 123 7	Duplex Outlet Box w/GFCI (F)*	12	3.32	3	45 14	SJEOOW	125	15	29 13	1
	L 5550 123 7	Duplex Outlet Box w/GFCI (F)*	12	3.32	3	50 15	SEOOOW	125	15	45 20	3
	L 70075 123 7	Duplex Outlet Box w/GFCI (F)*	12	3.32	3	75 23	SEOOOW	125	15	72 33	5
	L 70100 123 7	Duplex Outlet Box w/GFCI (F)*	12	3.32	3	100 30	SEOOOW	125	15	76 34	5
	L 4545 123 7A	Duplex Outlet Box w/GFCI (F)*	12	3.32	3	45 14	SJEOOW	125	20	29 13	1
	L 70075 123 7A	Duplex Outlet Box w/GFCI (F)*	12	3.32	3	75 23	SEOOOW	125	20	72 33	5
	L 70100 123 7A	Duplex Outlet Box w/GFCI (F)*	12	3.32	3	100 30	SEOOOW	125	20	76 34	5
	L 4545 123 7B	Duplex Outlet Box	12	3.32	3	45 14	SJEOOW	125	20	29 13	1
	L 4050 163 9	Triple Tap	16	1.33	3	50 15	SJEOOW	125	13	26 12	1
	L 4545 123 9	Triple Tap	12	3.32	3	45 14	SJEOOW	125	15	28 13	1
	L 70075 123 9	Triple Tap	12	3.32	3	75 23	SEOOOW	125	15	71 32	5
	L 70100 123 9	Triple Tap	12	3.32	3	100 30	SEOOOW	125	15	75 34	5
	L 4545 123 9G	Triple Tap w/GFCI (F)	12	3.32	3	45 14	SJEOOW	125	15	29 13	1
	L 70075 123 9G	Triple Tap w/GFCI (F)	12	3.32	3	75 23	SEOOOW	125	15	72 33	5
	L 70100 123 9G	Triple Tap w/GFCI (F)	12	3.32	3	100 30	SEOOOW	125	15	76 34	5

**For indoor non-weather tight applications only.** All models UL listed at 125 Volt 60 Hz single phase. \*The GFCI Receptacle is designed to protect from line-to-ground shock hazards. The Ground Fault Circuit Interrupter does not protect against short circuits or overloads; this is the function of the fuse or circuit breaker. Reference page 4 for guide arm positions. **NOTE:** Swing brackets should be used if cords are pulled at more than 45°, see page 47.

Flying Lead Model with Cord	Model No Cord	Cord Specifications				Volts/Amps	Volts/Amps	Shipping Weight*		Size Index #	
		AWG	mm <sup>2</sup>	# Cond.	ft m			Type	lbs		kg
	L 4050 163 X	L 4000	16	1.33	3	50 15	SJEOOW	125 / 13	220 / 6.5	22 10	1
	-----	L 4100	16	1.33	4	40 12	SJEOOW	125 / 13	220 / 6.5	22 10	1
	L 4545 123 X	L 4500	12	3.32	3	45 14	SJEOOW	125 / 20	220 / 10	22 10	1
	-----	L 5000	10	5.27	3	35 11	SO	125 / 30	220 / 15	29 13	2
	-----	L 5400	12	3.32	3	35 11	SJEOOW	125 / 13	220 / 6.5	25 11	2
	L 5550 123 X	L 5500	12	3.32	3	50 15	SEOOOW	125 / 20	220 / 10	35 16	3
	L 70075 123 X	L 70075	12	3.32	3	75 23	SEOOOW	125 / 20	220 / 10	69 31	6
	L 70100 123 X	L 70100	12	3.32	3	100 30	SEOOOW	125 / 20	220 / 10	73 33	6
	L 5550 124 X	-----	12	3.32	4	50 15	SEOOOW	-----	600 / 16	44 20	3
	L 70100 124 X	L 70100 124	12	3.32	4	100 30	SEOOOW	-----	600 / 16	75 34	6
	L 5750 103 X	L 5700	10	5.27	3	50 15	SEOOOW	125 / 30	220 / 15	37 17	4
	-----	L 7000	6	13.3	4	35 11	SOOW	-----	220 / 45	41 19	**
	L 7050 104 X	-----	10	5.27	4	50 15	SEOOOW	-----	600 / 20	65 29	**

**For indoor non-weather tight applications only.** All models UL listed at 125 Volt 60 HZ single phase. \*Weight of model without cord. \*\*Refer to reelcraft.com. Reference page 4 for guide arm positions.