

New Product Announcement | Series L 70000

Heavy Duty Spring Retractable Cord Reels Series L 70000

Reelcraft's new Series L 70000 cord reels are designed to accommodate up to 100 feet of 12 gauge cord. The heavy duty base design, all steel construction and a baked-on powder coat finish combine to produce a rugged, corrosion-resistant product. A newly redesigned latching mechanism provides longer service life of the latch components. The containerized drive spring offers safer and easier handling during maintenance. Two sealed ball bearings produce a smoother spool rotation and easier operation. The guide arm adjusts to seven positions for various mounting locations and applications.



NEW!

L 70100 123 9G

	Dimensions - Size Index			
	1		2	
	in	mm	in	mm
A	20 ¹ / ₄	514	20 ¹ / ₄	514
B	19 ³ / ₄	502	19 ³ / ₄	502
C	7 ¹³ / ₁₆	198	7 ¹³ / ₁₆	198
D	3 ⁷ / ₈	98	3 ⁷ / ₈	98
E	11 ³ / ₄	298	12 ¹ / ₂	318

- **Compact design** - Reels are 25% smaller than our heavy duty Series 80000 reels.
- **Guide rollers** - The one piece design and stainless steel pins offer greater strength and easier serviceability.
- **All-steel electrical enclosure** - Offers a stronger, more durable protective cover of electrical components.
- **UL listed** - All models UL listed from 10 - 20 Amps.

Model with Cord	Cord Ending	Cord Specifications						Volts	Amps	Shipping Weight		Size Index
		AWG	mm ²	# Cond	ft	m	Type			lbs	kg	
L 70075 123 3	Single Receptacle	12	3.32	3	75	23	SE00W	125	15	70	32	1
L 70100 123 3	Single Receptacle	12	3.32	3	100	30	SE00W	125	15	74	34	1
L 70075 123 3A	Single Receptacle	12	3.32	3	75	23	SE00W	125	20	70	32	1
L 70100 123 3A	Single Receptacle	12	3.32	3	100	30	SE00W	125	20	74	34	1
L 70075 123 3B	Twist Lock Connector	12	3.32	3	75	23	SE00W	125	20	70	32	1
L 70100 123 3B	Twist Lock Connector	12	3.32	3	100	30	SE00W	125	20	74	34	1
L 70075 123 7	Duplex Outlet Box w/GFCI*	12	3.32	3	75	23	SE00W	125	15	72	33	1
L 70100 123 7	Duplex Outlet Box w/GFCI*	12	3.32	3	100	30	SE00W	125	15	76	34	1
L 70075 123 7A	Duplex Outlet Box w/GFCI*	12	3.32	3	75	23	SE00W	125	20	72	33	1
L 70100 123 7A	Duplex Outlet Box w/GFCI*	12	3.32	3	100	30	SE00W	125	20	76	34	1
L 70075 123 9	Triple Tap	12	3.32	3	75	23	SE00W	125	15	71	32	1
L 70100 123 9	Triple Tap	12	3.32	3	100	30	SE00W	125	15	75	34	1
L 70075 123 9G	Triple Tap w/GFCI*	12	3.32	3	75	23	SE00W	125	15	72	33	1
L 70100 123 9G	Triple Tap w/GFCI*	12	3.32	3	100	30	SE00W	125	15	76	34	1

Flying Lead Model with Cord	Model without Cord	Cord Specifications						Volts/ Amps	Volts/ Amps	Shipping Weight**		Size Index
		AWG	mm ²	# Cond	ft	m	Type			lbs	kg	
L 70075 123 X	L 70075	12	3.32	3	75	23	SE00W	125 / 20	220 / 10	69	31	2
L 70100 123 X	L 70100	12	3.32	3	100	30	SE00W	125 / 20	220 / 10	73	33	2
L 70100 124 X	L 70100 124	12	3.32	4	100	30	SE00W	-----	600 / 16	75	34	2

For indoor non-weather tight applications only. All models UL listed at 125 Volt 60 HZ single phase. *The GFCI receptacle is designed to protect from line-to-ground shock hazards. The Ground Fault Circuit Interrupter does not protect against short circuits or overloads; this is the function of the fuse or circuit breaker. **Weight of model with cord.

Reelcraft Industries is
ISO 9001:2008
Certified Since 1996