

# New Product Announcement | Series RT

## Nitrogen Dispensing Reels Series RT

Reelcraft recognizes the growing demand for nitrogen tire inflation and proudly offers our new model, RT650-OLPG designed specifically for dispensing nitrogen gas. The reel is available in red, black, green or white and is equipped with 50 feet of green 3/8" I.D. hose. The special green nitrogen hose differentiates the reel from other air, water and oil reels that may be located in the same vicinity. Reelcraft's resilient powder coat finish keeps the reel looking new through years of use.

### Benefits

- **Lightweight** - Spool reduces overall weight without sacrificing strength.
- **Maximum Strength** - Structural reinforcements throughout increase strength and eliminate the need for a dual base.
- **Versatile Mounting Options** - Allow for pit, ceiling, wall, bench, or floor mount.
- **Ease of Use** - The possibility of hose latch-out at full extension of hose has virtually been eliminated due to mounting the latching mechanism on the guide arm.
- **Long Service Life** - Stainless torsion spring ensures maximum life and requires less maintenance.
- **Weather Resistant** - Powder coat finish provides exceptional protection and keeps reels looking new through years of use.
- **Safety** - Hose and reel color differentiates nitrogen reel from others located nearby.

### Related Products

The Series RT offers a multitude of different lengths and I.D.s for air, water, and oil applications. The nitrogen hose assembly may be purchased by itself. For more information visit us online at [www.reelcraft.com](http://www.reelcraft.com) or call toll free 800-444-3134.



RT650-OLPG-35BK



		Dimensions	
		in	mm
<b>A</b>	17 <sup>7</sup> / <sub>8</sub>	454	
<b>B</b>	16 <sup>1</sup> / <sub>2</sub>	419	
<b>C</b>	6	152	
<b>D</b>	2 <sup>1</sup> / <sub>4</sub>	57	
<b>E</b>	6 <sup>1</sup> / <sub>4</sub>	159	

- 30% glass-filled composite spool
- Reinforced base and guide arm made from heavy gauge steel stampings
- Latch mechanism mounted on guide arm for longer life
- Seven mounting positions
- Stainless steel torsion spring
- Baked on powder coat paint
- Bright green hose

Model with hose	Color	Shipping Weight		Hose I.D.		Hose O.D.		Hose Length		Pressure	
		lbs	kg	in	mm	in	mm	ft	m	psi	bar
<b>Nitrogen Reels</b> Maximum temperature 150 °F (65 °C) - Reel inlet is 1/2" (F)NPTF											
RT650-OLPG	Red	29	14	3/8	10	.625	16	50	15	300	21
RT650-OLPG-35BK	Black	29	14	3/8	10	.625	16	50	15	300	21
RT650-OLPG-20GN	Green	29	14	3/8	10	.625	16	50	15	300	21
RT650-OLPG-17WH	White	29	14	3/8	10	.625	16	50	15	300	21

Hose Assembly	Shipping Weight		Hose I.D.		Hose O.D.		Hose Length		Pressure	
	lbs	kg	in	mm	in	mm	ft	m	psi	bar
601055-50	7	3	3/8	10	.625	16	50	15	300	21