

# New Product Announcement | Twin Pack Reels

## Twin Pack Reels Air / Water and Electric

Reelcraft now offers its most popular hose and cord reel models as a convenient package. Reelcraft twin packs are ideal for customers looking to outfit a bench/work station with both power/lighting and pneumatics. It is now even easier to order with only one part number, one price and combine on shipping. Other model combinations are available upon request.

### Benefits

- **Improved Efficiency** - Air and power where and when you need it
- **Increased Safety** - Reduce injury incidence due to slips, trips and falls
- **Improved Productivity** - Less time spent managing unwieldy coiled hoses and cords
- **Reduce Hose Wear** - Store hoses and cords out of harms way

### Related Products

Reelcraft offers a comprehensive line of hose, cord and cable reels for almost every application. For more information visit us online at [www.reelcraft.com](http://www.reelcraft.com) or contact a customer service representative at 1-855-634-9109.



Model Shown:  
TP5650 OLP/L 4545 123 3



in USA

Model	Hose I.D.		Hose Length		Pressure		Cord Specifications					Volts	Amps	Accessory	
	in	mm	ft	m	psi	bar	AWG	mm	# Cond	ft	m				Type
<b>Economic Air/Water &amp; Electric Reels</b> Max temperature 150 °F (65 °C)															
TPRT635-OLP/LD2030 143 9	3/8	10	35	11	300	21	14	2.08	3	30	9	SJTW	125	13	Grounded Triple Outlet
TPRT650-OLP/LG3050 143 9	3/8	10	50	15	300	21	14	2.08	3	50	15	SJTW	125	13	Grounded Triple Outlet
TPRT635-OLP/LG3050 163 8	3/8	10	35	11	300	21	16	1.33	3	50	15	SJTW	120	10	13 watt FL Light w/ Outlet
TPRT650-OLP/LG3050 163 8	3/8	10	50	15	300	21	16	1.33	3	50	15	SJTW	120	10	13 watt FL Light w/ Outlet
TPRT650-OLP/LD2040 163 2	3/8	10	50	15	300	21	16	1.33	2	40	12	SJTW	120	0.3	13 watt FL Light
TPRT650-OLP/L 4545 123 3	3/8	10	50	15	300	21	12	3.32	3	45	14	SJEOOW	125	15	Single Receptacle
TPRT650-OLP/L 4545 123 7	3/8	10	50	15	300	21	12	3.32	3	45	14	SJEOOW	125	15	Duplex Outlet Box w/ GFCI
TP4625 OLP/LD2030 143 9	3/8	10	25	8	300	21	14	2.08	3	30	9	SJTW	125	13	Grounded Triple Outlet
TP4625 OLP/LD2040 163 2	3/8	10	25	8	300	21	16	1.33	3	30	9	SJTW	120	0.3	13 watt FL Light
<b>Premium Air/Water &amp; Electric Reels</b> Max temperature 150 °F (65 °C)															
TP5635 OLP/LG3040 123 9	3/8	10	35	11	300	21	12	3.32	3	40	12	SJTW	125	15	Grounded Triple Outlet
TP5635 OLP/L 4545 123 3	3/8	10	35	11	300	21	12	3.32	3	45	14	SJEOOW	125	15	Single Receptacle
TP5650 OLP/L 4050 163 3	3/8	10	50	15	300	21	16	1.33	3	50	15	SJTOW	125	13	Single Receptacle
TP5650 OLP/L 4545 123 3	3/8	10	50	15	300	21	12	3.32	3	45	14	SJEOW	125	15	Single Receptacle
TP5650 OLP/L 4545 123 7	3/8	10	50	15	300	21	12	3.32	3	45	14	SJEOOW	125	15	Duplex Outlet Box w/ GFCI
TP5650 OLP/L 4050 163 1	3/8	10	50	15	300	21	16	1.33	3	50	15	SJTOW	125	13	Incandescent Light w/ Outlet
TP5635 OLP/L 4035 163 8	3/8	10	35	11	300	21	12	3.32	3	35	11	SJTO	125	10	13 watt FL Light w/ Outlet
TP5650 OLP/L 4050 163 8	3/8	10	50	15	300	21	12	3.32	3	50	15	SJTO	125	10	13 watt FL Light w/ Outlet
TP5650 OLP/L 4050 162 2	3/8	10	50	15	300	21	12	3.32	2	50	15	SJTOW	125	0.3	13 watt FL Light
<b>Heavy Duty Industrial Air/Water &amp; Electric Reels</b> Max temperature 150 °F (65 °C)															
TP7650 OLP/L 4545 123 3	3/8	10	50	15	300	21	12	3.32	3	45	14	SJEOOW	125	15	Single Receptacle
TP7650 OLP/L 4545 123 7	3/8	10	50	15	300	21	12	3.32	3	45	14	SJEOOW	125	15	Duplex Outlet Box w/ GFCI
TP7650 OLP/L 4050 163 8	3/8	10	50	15	300	21	16	1.33	3	50	15	SJTO	125	10	13 watt FL Light w/ Outlet
TP7670 OLP/L 4545 123 3A	3/8	10	70	22	300	21	12	3.32	3	45	14	SJEOOW	125	20	20 AMP Single Receptacle
TP7670 OLP/L 5550 123 7	3/8	10	70	22	300	21	12	3.32	3	50	15	SJEOOW	125	15	Duplex Outlet Box w/ GFCI
TP7850 OLP/L 4545 123 3A	1/2	13	50	15	300	21	12	3.32	3	45	14	SJEOOW	125	20	20 AMP Single Receptacle
TP7850 OLP/L 4545 123 7A	1/2	13	50	15	300	21	12	3.32	3	45	14	SJEOOW	125	20	Duplex Outlet Box w/ GFCI
TP7850 OLP/L 5550 123 7	1/2	13	50	15	300	21	12	3.32	3	50	15	SJEOOW	125	15	Duplex Outlet Box w/ GFCI

NOTE: Electric reels rated for indoor non-weather tight applications. Consult our main catalog or a member of customer service for additional reel specifications.